

MIAMI-DADE COUNTY PRODUCT CONTROL SECTION

DEPARTMENT OF PERMITTING, ENVIRONMENT, AND REGULATORY AFFAIRS (PERA)
BOARD AND CODE ADMINISTRATION DIVISION

11805 SW 26 Street, Room 208 Miami, Florida 33175–2474 T (786) 315–2590 F (786) 315–2599

www.miamidade.gov/pera

NOTICE OF ACCEPTANCE (NOA)

Momentive Performance Materials USA Inc. 22 Corporate Woods Blvd. Albany, NY 12211-2374

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami–Dade County PERA – Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami–Dade County Product Control Section (In Miami–Dade County) and/or the AHJ (in areas other than Miami–Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. PERA reserves the right to revoke this acceptance, if it is determined by Miami–Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: SCM3400 Series Silicone Coatings.

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state, model/ series and following statement: "Miami–Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami–Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA No. 10-1112.03 and consists of pages 1 through 3.

The submitted documentation was reviewed by Jorge L. Acebo.



Son W

NOA No.: 11-1007.01 Expiration Date: 04/29/14 Approval Date: 01/26/12

Page 1 of 3

ROOFING COMPONENT APPROVAL

<u>Category:</u> Roofing

<u>Sub-Category:</u> Cement-Adhesive-Coatings

Material: Silicon

SCOPE:

This approves "SCM3400 Series Silicone Coatings" as a roof coating as manufactured by Momentive Performance Materials USA Inc, as described in this Notice of Acceptance, designed to comply with the Florida Building Code and the High Velocity Hurricane Zone of the Florida Building Code

EVIDENCE SUBMITTED:

Test Agency	Test Identifier	Test Name/Report	<u>Date</u>
PRI Construction Materials Technologies, LLC	MPM-001-02-01	ASTM D 6694 TT-C-555B	10/08/10

MANUFACTURING LOCATION:

1. Waterford, NY

PHYSICAL PROPERTIES OF COMPONENTS

Trade names: SCM3400 Series Silicone Coatings

SCM3402 (White)

SCM3404 (Medium Grey)

SCM3405 (Tan)

SCM3408 (Dark Grey)

Thickness: See System Approvals Below

Specifications: ASTM D 6694

Description: A silicone-based elastomeric coating membrane of various colors applied at an

application rate of;

• Foam Roofs: Apply Base Coat at a minimum rate of 2.5 gal/100 ft² and Top

Coat at a rate of 2.5 gal/100 ft².

Container Size: 5 and 55 gallons. Note all precautions on container.

Systems Approvals: Methods of application and quantities shall comply with specific Roof

Assembly, Product Control Notice of Acceptance.



NOA No.: 11-1007.01 Expiration Date: 04/29/14 Approval Date: 01/26/12 Page 2 of 3

LIMITATIONS:

- 1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire rating of this product.
- 2. SCM3400 Series Silicone shall not be applied in inclement weather conditions.
- 3. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list any of the products listed herein as part of their roof assemblies Notice of Acceptance.
- 4. All products listed herein shall have an unannounced follow-up quality control program from an approved listing agency. Follow up test results shall be made available to BCCO upon request.
- 5. Change in materials, use, or manufacture of any of the products listed herein shall be cause for termination of this Notice of Acceptance.
- 6. SCM3400 Series Silicone shall be applied in accordance with manufacturer's published application instructions.
- 7. All products listed herein shall have a quality assurance audit in accordance with the Florida Building Code and Rule 9N-3 of the Florida Administrative Code.
- 8. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo as follows, "Momentive Performance Materials Inc", and the following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



END OF THIS ACCEPTANCE



NOA No.: 11-1007.01 Expiration Date: 04/29/14 Approval Date: 01/26/12

Page 3 of 3